PCCH35IR

sk microworks Window Film

1. Increase personal privacy Adhesive 2. Better eye comfort Optical Grade PET Film (12±1/m) 3. Great maintenance with less scratch UN(C + DCA)	4. Long life indoor fabric from fading UV-Cut PSA
Silicone Release Film(23µm)	

_			150 9050		I	I
Visible Light	External	6.1%	KS L 2016	Thickness	1.5Mil/2Ply	
Reflected Solar Heat	Internal	5.9%	ISO 9050 ISO 9050	Shading Coefficient	0.61	JIS A 5759
	Reflected	5.6%		Solar Heat Gain	0.54	KS L 2514
	Absorbed	58.1%		Coefficient (SHGC)		
	Transmitted	36.3%		Scratch Resistant	>2H	ASTM D3363
IR Rejected		55%	ISO 9050	Haze	1.4%	ASTM D1003
UV Rejected		99% ↑	KS L 2016 ISO 9050	Adhesion of Hard-Coated Surface	5B (0% peel-off)	ASTM D3359
Total Solar Energy Rejected (TSER) 50.8		50.8.%	ISO 9050			

This information is the best currently available on the subject. The result should, however, only be regarded as a general guide to material properties and not as a guarantee. Some of the properties can be changed as a result of supplier's effort to improve the quality or production efficiency of the subject.