TC 1095

sk microworks Window Film

Advantage -

- 1. Drive cooler by reducing excessive solar heat
- 2. Better eye comfort
- 3. Great maintenance with less scratch
- 4. Long life indoor fabric from fading

Clear Hard-Coating

Optical Grade PET Film (23±1/m)

Adhesive

Optical Grade PET Film (23±1/m)

UV-Cut PSA

Silicone Release Film(23µm)

Visible Light Transmitted		6.3%	KS L 2016 ISO 9050			1
Visible Light	External	4.6%	KS L 2016	Thickness	2Mil/2Ply	
Reflected Solar Heat	Internal	4.7%	ISO 9050 ISO 9050	Shading Coefficient	0.42	JIS A 5759
	Reflected	4.7%				
	Absorbed	89%		Solar Heat Gain	0.37	KS L 2514
	Transmitted	6.3%		Coefficient (SHGC)		
IR Rejected		97%	ISO 9050	Scratch Resistant	>2H	ASTM D3363
UV Rejected		99%	KS L 2016 ISO 9050	Adhesion of Hard-Coated Surface	5B (0% peel-off)	ASTM D3359
Total Solar Energy Rejected (TSER)		70.3%	ISO 9050		1	I

This information is the best currently available on the subject. The result should, however, only be regarded as a general guide to material properties and not as a guarantee. Some of the properties can be changed as a result of supplier's effort to improve the quality or production efficiency of the subject.