

# WVA4035



## Window Film

### Advantage -

1. Drive cooler by reducing excessive solar heat
2. Better eye comfort
3. Great maintenance with less scratch
4. Long life indoor fabric from fading

IR-Cut Hard-Coating

Chip-Dyed PET Film (23±1μm)

UV-Cut PSA

Silicone Release Film(23μm)

Visible Light Transmitted		39%	ASTM E424 KS L 2016
Visible Light Reflected	External	5%	ASTM E424 KS L 2016
	Internal	6%	
Solar Heat Reduction		34%	ASTM E424
Solar Heat	Reflected	5%	ASTM E424 KS L 2016
	Absorbed	52%	
	Transmitted	43%	
IR Transmitted		60%	ASTM E424
UV Rejected		99%↑	ASTM E424
Glare Reduction		56%	ASTM E424 KS L 2016
Total Solar Energy Rejected (TSER)		43%	ASTM E424

Thickness	1Mil/ 1Ply	
Shading Coefficient	0.66	ASTM E424
Solar Heat Gain Coefficient (SHGC)	0.57	ASTM E424
Scratch Resistant	> 2H	ASTM D3363
Haze	0.6 %	ASTM D1003
Adhesion of Hard-Coated Surface	5B (0% peel-off)	ASTM D3359