WVP20

sk microworks Window Film

Advantage -

- 1. Increase personal privacy
- 2. Better eye comfort
- 3. Great maintenance with less scratch
- 4. Long life indoor fabric from fading

Clear Hard-Coating

Optical Grade PET Film (23±1μm)

Adhesive

Optical Grade PET Film (12±1µm)

UV-Cut PSA

Silicone Release Film(23µm)

Visible Light Transmitted		17%	KS L 2016 ISO 9050			
Visible Light Reflected	External	5.3%	KS L 2016 ISO 9050	Thickness	1.5Mil/2Ply	
	Internal	5%				
Solar Heat Reduction		38%		Shading Coefficient	0.62	KS L 2016
Solar Heat	Reflected	5.6%	ISO 9050	Solar Heat Gain Coefficient (SHGC)	0.57	KS L 2514
	Absorbed	60.7%				
	Transmitted	33.7%		Scratch Resistant	>2H	ASTM D3363
IR Transmitted		52%	ISO 9050	Haze	1.4%	ASTM D1003
UV Rejected		99% ↑	KS L 2514	Adhesion of Hard-Coated Surface		ASTM D3359
			ISO 9050		5B	
Total Solar Energy Rejected (TSER)		50.3%	ISO 9050		(0% peel-off)	

This information is the best currently available on the subject. The result should, however, only be regarded as a general guide to material properties and not as a guarantee. Some of the properties can be changed as a result of supplier's effort to improve the quality or production efficiency of the subject.