

WVS35



Window Film

Advantage -

1. Drive cooler by reducing excessive solar heat
2. Better eye comfort
3. Great maintenance with less scratch
4. Long life indoor fabric from fading

Clear Hard-Coating

Optical Grade PET Film (75±1μm)

Adhesive

Chip-Dyed PET Film (23±1μm)

UV-Cut PSA

Silicone Release Film(23μm)

Visible Light Transmitted		30%	ASTM E424 KS L 2016
Visible Light Reflected	External	6%	ASTM E424 KS L 2016
	Internal	5%	
Solar Heat Reduction		25%	ASTM E424
Solar Heat	Reflected	7%	ASTM E424 KS L 2016
	Absorbed	38%	
	Transmitted	55%	
UV Rejected		99.4%	ASTM E424
Glare Reduction		68%	ASTM E424 KS L 2016
Total Solar Energy Rejected (TSER)		35%	ASTM E424

Thickness	4Mil/2Ply	
Shading Coefficient	0.75	ASTM E424
Solar Heat Gain Coefficient (SHGC)	0.65	ASTM E424
Scratch Resistant	>2H	ASTM D3363
Haze	1.3%	ASTM D1003
Adhesion of Hard-Coated Surface	5B (0% peel-off)	ASTM D3359